United State . America



To Promote the Progress

of Science and Useful Arts

The Director

of the United States Patent and Trademark Office has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this United States

grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America, and if the invention is a process, of the right to exclude others from using, offering for sale or selling throughout the United States of America, products made by that process, for the term set forth in 35 U.s.c. 154(a)(2) or (c)(1), subject to the payment of maintenance fees as provided by 35 U.s.c. 41(b). See the Maintenance Fee Notice on the inside of the cover.



Kathevine Kelly Vidal

Director of the United States Patent and Trademark Office

Maintenance Fee Notice

If the application for this patent was filed on or after December 12, 1980, maintenance fees are due three years and six months, seven years and six months, and eleven years and six months after the date of this grant, or within a grace period of six months thereafter upon payment of a surcharge as provided by law. The amount, number and timing of the maintenance fees required may be changed by law or regulation. Unless payment of the applicable maintenance fee is received in the United States Patent and Trademark Office on or before the date the fee is due or within a grace period of six months thereafter, the patent will expire as of the end of such grace period.

Patent Term Notice

If the application for this patent was filed on or after June 8, 1995, the term of this patent begins on the date on which this patent issues and ends twenty years from the filing date of the application or, if the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121, 365(c), or 386(c), twenty years from the filing date of the earliest such application ("the twenty-year term"), subject to the payment of maintenance fees as provided by 35 U.S.C. 41(b), and any extension as provided by 35 U.S.C. 154(b) or 156 or any disclaimer under 35 U.S.C. 253.

If this application was filed prior to June 8, 1995, the term of this patent begins on the date on which this patent issues and ends on the later of seventeen years from the date of the grant of this patent or the twenty-year term set forth above for patents resulting from applications filed on or after June 8, 1995, subject to the payment of maintenance fees as provided by 35 U.S.C. 41(b) and any extension as provided by 35 U.S.C. 156 or any disclaimer under 35 U.S.C. 253.



US012091237B2

(12) United States Patent

Vallee et al.

(54) FLOATING ROOF ADJUSTABLE DECK POSITIONERS

- (71) Applicant: Sandborn Roof Inc., Nisku (CA)
- (72) Inventors: Dave Vallee, Nisku (CA); Elias Lopez, Nisku (CA)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 6 days.
- (21) Appl. No.: 18/083,003
- (22) Filed: Dec. 16, 2022

(65) **Prior Publication Data**

US 2023/0202748 A1 Jun. 29, 2023

Related U.S. Application Data

- (60) Provisional application No. 63/293,449, filed on Dec. 23, 2021.
- (51) Int. Cl. *B65D 88/36* (2006.01)
- (52) U.S. Cl. CPC *B65D 88/36* (2013.01)
- (58) Field of Classification Search CPC B65D 88/36; B65D 88/34; B65D 88/38; B65D 88/40; B65D 88/42; B65D 88/44; B65D 88/46; B65D 88/48; B65D 88/50

See application file for complete search history.

(10) Patent No.: US 12,091,237 B2 (45) Date of Patent: Sep. 17, 2024

References Cited

U.S. PATENT DOCUMENTS

5,029,932	A *	7/1991	Parr B60J 7/143
			296/108
5,321,881	Α *	6/1994	Lippiello B65D 88/46
			29/525.04
5,529,200	A *	6/1996	Ford B65D 88/46
			220/226
6,164,479	A *	12/2000	Kern B65D 88/46
			220/216
9,555,959	B1 *	1/2017	Ziegs B65D 88/005
2014/0061204	A1*	3/2014	Ziegs B65D 90/028
			29/592
2016/0031637	A1*	2/2016	Bretherton B65D 88/46
			220/222
2017/0121103	A1*	5/2017	Ellis B65D 88/42
2020/0024068	A1*	1/2020	MacLeod E04G 1/34
2021/0080310	A1*	3/2021	Frövik B65D 90/48

* cited by examiner

(56)

Primary Examiner - Kareen K Thomas

(74) Attorney, Agent, or Firm - Bennett Jones LLP

(57) ABSTRACT

An adjustable deck positioner includes a vertical member having means for attaching to a deck rim and having a pivot arm bracket; a pivot arm assembly having a pivot arm attached to the pivot arm bracket, wherein the pivot arm may pivot between a substantially vertical position within the pivot arm bracket and an extended position angled away from the vertical member; and a lock pin installed across the pivot arm bracket, for constraining movement of the pivot arm towards the vertical member, thereby setting the angle at which the pivot arm extends from the vertical member.

6 Claims, 3 Drawing Sheets





Figure 1



Figure 2



Figure 3



Figure 4

10

15

60

FLOATING ROOF ADJUSTABLE DECK POSITIONERS

FIELD OF THE INVENTION

The present invention relates to an adjustable deck positioning system for a floating roof.

BACKGROUND OF THE INVENTION

Field erected storage tanks are commonly used to store large quantities of petrochemicals including both refined and unrefined products. The tank has a cylindrical steel shell and a roof that floats on the surface of the stored liquid, which reduces emissions and evaporative product loss. The roof rises and falls with the liquid level in the tank. There is a rim seal system between the tank shell and floating roof to reduce rim evaporation.

The floating roof deck typically will include deck positioners which maintain a separation distance between the deck and the inside wall of the storage tank. This gap allows the primary and secondary seals to work properly as the floating roof deck travels vertically within the tank. Installation of the positioners typically involved drilling, welding 25 and/or bolting a series of "spacers", set at a fixed distance. Re-work or replacement would be required should the fixed distance need adjusting or the positioners require a location change.

There is a need in the art for a deck positioner which may ³⁰ mitigate difficulties presented by the prior art.

SUMMARY OF THE INVENTION

In summary, embodiments of the present invention allows ³⁵ for quick and simple adjustments to adjust the deck/tank gap distance as required by tank/seal conditions and/or desired configurations. Furthermore, embodiments of the invention provide a bolted design which allows for quick removal and repositioning. ⁴⁰

In one aspect, the invention comprises an adjustable deck positioner comprising (a) a vertical member having means for attaching to a deck rim and having a pivot arm bracket; (b) a pivot arm assembly having a pivot arm attached to the pivot arm bracket, wherein the pivot arm may pivot between 45 a substantially vertical position within the pivot arm bracket and an extended position angled away from the vertical member; and a lock pin installed across the pivot arm bracket, for constraining movement of the pivot arm towards the vertical member, thereby setting the angle at which the 50 pivot arm extends from the vertical member.

In some embodiments, the pivot arm bracket is U-shaped, defining a channel between opposing fins which define a plurality of pairs of vertically spaced lock pin openings. The lock pin is inserted horizontally into a pair of lock pin ⁵⁵ openings, thus maintaining the pivot arm at an angle away from the vertical member.

The pivot arm assembly has a tank engaging element which may comprise a low-friction material or a wheel, which preferably comprises a low-friction material.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, like elements may be assigned like reference numerals. The drawings are not necessarily to 65 scale, with the emphasis instead placed upon the principles of the present invention. Additionally, each of the embodi-

ments depicted are but one of a number of possible arrangements utilizing the fundamental concepts of the present invention.

FIG. 1 shows a perspective view of an embodiment of an adjustable deck positioner having a horizontal attachment flange. FIG. 1A shows an alternative vertical attachment flange.

FIG. **2** shows a side plan view of the embodiment of FIG. **1**.

FIG. **3** shows a top plan view of a floating roof deck, with a detailed top plan view of the embodiment of FIG. **1**.

FIG. 4 shows a side cross-sectional view of the floating roof deck of FIG. 3.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

The invention relates to an adjustable deck positioning system for a floating roof tank (T). The tank is typically cylindrical with a substantially circular horizontal crosssection. The floating roof is thus a substantially circular member that moves upwards and downwards within the storage tank. The deck (1) is the primary structural element of a floating roof, closely fitting within the storage tank, and includes pontoons, as is well known in the art. The configuration of sealing systems and the floating roof are not essential elements of the present invention.

FIGS. 1 and 2 show an exemplary embodiment of an adjustable deck positioner (10), which comprises:

- (a) a vertical member (12) having means for attaching (14) to a deck rim (2) and having a pivot arm bracket (16);
- (b) a pivot arm assembly (18) having a pivot arm (20) pivotably attached to the pivot arm bracket (16), wherein the pivot arm is moveable between a substantially vertical position within the pivot arm bracket, and an extended position extending away from the vertical member; and
- (c) a lock pin (22) installed across the pivot arm bracket, for constraining movement of the pivot arm towards the vertical member, thereby setting the angle at which the pivot arm extends from the vertical member.

In some embodiments, the means for attaching to a deck may comprise an attachment flange (14) which bolts to a deck rim (2), as shown in FIG. 2. In alternative embodiments, the attachment flange (14) may be vertical, as shown in FIG. 1A. Any physical attachment structure may be suitable. It is preferred that the deck positioner (10) be removably attached, permitting convenient removal and repositioning.

In some embodiments, the pivot arm bracket (16) is U-shaped, defining a channel between opposing fins (24) which define a plurality of vertically spaced lock pin openings (26). The embodiment shown in FIG. 2 has six pairs of lock pin openings (26), and the lock pin (22) is inserted in the openings (26) third from the top. The lock pin (22) when inserted horizontally into the lock pin openings will maintain the pivot arm at an angle away from the vertical member, as may be seen in FIG. 2. As the lock pin opening gets closer to the pivot axis (P) of the pivot arm, it will maintain the pivot arm in a more extended position (more horizontal).

The pivot arm assembly (18) has a tank engaging element (30) contacts the inner surface of the tank and moves upwards and downwards with the deck (1). The tank engaging element (30) preferably comprises a low-friction material, such as a smooth plastic, eg. nylon or a PTFE material.

25

The tank engaging element more preferably comprises a roller wheel (30), which itself may comprise a low-friction material.

As shown in FIG. 3, the adjustable deck positioners (10) are arrayed around the circumference of the deck (1) at 5 predefined locations. The number and spacing of deck positioners may be varied as necessary or desired to meet design parameters. The exemplary embodiment shown in FIG. **3** has 12 deck positioners spaced apart at 30° intervals.

In some embodiments, the deck rim (2) has pre-drilled or 10 formed bolt openings, and the adjustable deck positioners may be bolted to the deck rim with removable fasteners. Thus, the adjustable deck positioners may be removed and repositioned by simply unbolting and bolting in the new desired position.

As may be seen in FIG. 4, the adjustable deck positioners (10) will act to maintain a gap between the deck edge and the inner surface of the tank (T). The deck positioner shown in the right hand side has the lock pin (22) inserted into the uppermost pair of lock pin openings, thereby extending the 20 pivot arm (20) to its most extended position. The deck positioner shown in the left hand side has the lock pin (22) inserted into the 2' lowermost pair of lock pin openings, thereby extending the pivot arm (20) in a more retracted position.

Interpretation.

References in the specification to "one embodiment", "an embodiment", etc., indicate that the embodiment described may include a particular aspect, feature, structure, or characteristic, but not every embodiment necessarily includes 30 that aspect, feature, structure, or characteristic. Moreover, such phrases may, but do not necessarily, refer to the same embodiment referred to in other portions of the specification. Further, when a particular aspect, feature, structure, or characteristic is described in connection with an embodi- 35 ment, it is within the knowledge of one skilled in the art to affect or connect such module, aspect, feature, structure, or characteristic with other embodiments, whether or not explicitly described. In other words, any module, element or feature may be combined with any other element or feature 40 in different embodiments, unless there is an obvious or inherent incompatibility, or it is specifically excluded.

It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for the use of exclusive 45 terminology, such as "solely," "only," and the like, in connection with the recitation of claim elements or use of a "negative" limitation. The terms "preferably," "preferred," "prefer," "optionally," "may," and similar terms are used to indicate that an item, condition or step being referred to is 50 an optional (not required) feature of the invention.

The singular forms "a," "an," and "the" include the plural reference unless the context clearly dictates otherwise. The term "and/or" means any one of the items, any combination of the items, or all of the items with which this term is 55 associated. The phrase "one or more" is readily understood by one of skill in the art, particularly when read in context of its usage.

The term "about" can refer to a variation of $\pm 5\%$, $\pm 10\%$, $\pm 20\%$, or $\pm 25\%$ of the value specified. For example, "about 4

50" percent can in some embodiments carry a variation from 45 to 55 percent. For integer ranges, the term "about" can include one or two integers greater than and/or less than a recited integer at each end of the range. Unless indicated otherwise herein, the term "about" is intended to include values and ranges proximate to the recited range that are equivalent in terms of the functionality of the composition, or the embodiment.

As will be understood by one skilled in the art, for any and all purposes, particularly in terms of providing a written description, all ranges recited herein also encompass any and all possible sub-ranges and combinations of sub-ranges thereof, as well as the individual values making up the range, particularly integer values. A recited range includes each specific value, integer, decimal, or identity within the range. Any listed range can be easily recognized as sufficiently describing and enabling the same range being broken down into at least equal halves, thirds, quarters, fifths, or tenths. As a non-limiting example, each range discussed herein can be readily broken down into a lower third, middle third and upper third, etc.

As will also be understood by one skilled in the art, all language such as "up to", "at least", "greater than", "less than", "more than", "or more", and the like, include the number recited and such terms refer to ranges that can be subsequently broken down into sub-ranges as discussed above. In the same manner, all ratios recited herein also include all sub-ratios falling within the broader ratio.

The invention claimed is:

1. An adjustable deck positioner for a floating roof tank comprising:

- (a) a vertical member having means for attaching to a deck rim and having a pivot arm bracket;
- (b) a pivot arm assembly having a pivot arm attached to the pivot arm bracket, wherein the pivot arm pivots between a substantially vertical position within the pivot arm bracket and an extended position angled away from the vertical member; and
- (c) a lock pin installed across the pivot arm bracket, for constraining movement of the pivot arm towards the vertical member, thereby setting the angle at which the pivot arm extends from the vertical member.

2. The adjustable deck positioner of claim 1 wherein the means for attaching to a deck rim comprises a horizontal or vertical flange bolted to the deck rim.

3. The adjustable deck positioner of claim 1 wherein the pivot arm bracket comprises a U-shaped channel formed between opposing fins which define a plurality of vertically spaced lock pin openings.

4. The adjustable deck positioner of claim 1 wherein the pivot arm comprises a tank engaging element.

5. The adjustable deck positioner of claim 4 wherein the tank engaging element comprises a low-friction material or a roller wheel.

6. A floating roof deck having a plurality of adjustable deck positioners as claimed in claim 1 installed around its circumference.

*